



Typology Utilisation Pendant Indoor



Hanging lamp, diffused light, composed with curved sectors in painted aluminium profile. The union of those sectors offer different diameters rings, hanged by stainless steel cables. White opal polycarbonate diffuser. Integrated LED light source. Electronic dimmable Push/Dali, 0-10V e 1-10V driver inside in the canopy. Available on request 2700K, 4000K.

interior light emission:

21003/500/DIM Ø 500cm composed by 6 sectors 60°

21003/400/DIM Ø 400cm composed by 5 sectors 72°

21003/300/DIM Ø 300cm composed by 4 sectors 90°

21003/200/DIM Ø 200cm composed by 3 sectors 120°

21003/160/DIM Ø 160cm composed by 3 sectors 120°


Loop 2100	Loop 21003/200/DIM		Data Sheet		
Family Typology Utilisation	Loop Pendant Indoor			_	
Dimensions					
Diameter	200 cm				
Weight	18 Kg				
Materials					
Structure	aluminium	Diffuser		polycarbonate	
Voltage	230V	Watt	271.2 W		
Power unit		Lumen	24868 lm		
Mounting Power Supply	External	CRI CCT	>80 3000 K		
Power supply	Electronic dimmable power supply	Energy class			
Dimming	Push	01055			
	Dali2				
	Pot. 10KΩ				

Certifications





Photometric curves



0-10V 1-10V



Colour variant code



21003/200/DIM/BI



21003/200/DIM/NE







21003/200/DIM/AU





