



Typology Utilisation Pendant Indoor



Hanging lamp, diffused light, composed with curved sectors in painted aluminium profile. The union of those sectors offer different diameters rings, hanged by stainless steel cables. White opal polycarbonate diffuser. Integrated LED light source. Electronic dimmable Push/Dali, 0-10V e 1-10V driver inside in the canopy. Available on request 2700K, 4000K.

interior light emission:

21003/500/DIM Ø 500cm composed by 6 sectors 60°

21003/400/DIM Ø 400cm composed by 5 sectors 72°


21003/300/DIM Ø 300cm composed by 4 sectors 90°

21003/200/DIM Ø 200cm composed by 3 sectors 120°

21003/160/DIM Ø 160cm composed by 3 sectors 120°

| Loop 21003/400/DIM | | Data Sheet | |
|-----------------------------------|---------------------------|------------|---------------|
| Family Typology Utilisation | Loop Pendant Indoor | | |
| Dimensions | | | |
| Height | 8 cm | | |
| Diameter | 400 cm | | |
| Power supply cable length | 400 cm | | |
| Weight | 35 Kg | | |
| Materials | | | |
| Structure | aluminium | Diffuser | polycarbonate |
| Voltage | 230V | Watt | 543 W |
| Power unit | Included | Lumen | 49777 lm |
| Mounting Power Supply | , External | CRI CCT | >80 3000 K |
| Power supply | Electronic power supply | Energy | |
| Dimming | Push | class | |
| Dimining | Dali2 | | |
| | Pot. 10KΩ | | |
| | 0-10V | | |
| | 1-10V | | |
| Certifications | | EcoLabel | |





Colour variant code

