



Typology Utilisation Pendant Indoor



Hanging lamp, diffused light, composed with curved sectors in painted aluminium profile. The union of those sectors offer different diameters rings, hanged by stainless steel cables. White opal polycarbonate diffuser. Integrated LED light source. Electronic dimmable Push/Dali, 0-10V e 1-10V driver inside in the canopy. Available on request 2700K, 4000K.

interior light emission:

21003/500/DIM Ø 500cm composed by 6 sectors 60°

21003/400/DIM Ø 400cm composed by 5 sectors 72°

21003/300/DIM Ø 300cm composed by 4 sectors 90°

21003/200/DIM Ø 200cm composed by 3 sectors 120°

21003/160/DIM Ø 160cm composed by 3 sectors 120°


Loop 21003/300/DIM		Data Sheet			
Family Typology Utilisation	Loop Pendant Indoor				
Dimensions					
Height	8 cm				
Diameter	300 cm				
Power supply cable length	400 cm				
Weight	28 Kg				
Materials					
Structure	aluminium	Diffuser		polycarbonate	
Voltage	230V	Watt	406.9 W		
Power unit	Included	Lumen	37303 lm		
Mounting Power Supply	External	CRI CCT	>80 3000 K		
Power supply	Electronic dimmable power supply	Energy class			
Dimming	Push	01033			
	Dali2				
	Pot. 10KΩ 0-10V				
	0-10V 1-10V				

Certifications





Photometric curves





Colour variant code



21003/300/DIM/BI



21003/300/DIM/NE





21003/300/DIM/AU





