| | | Source |
|-------------------------|-----------------|------------------|
| Typology Utilisation | Floor Indoor | 24V 13 W 1950 Im |

A dynamic floor lamp with direct/indirect light. Thanks to the three guy wires fixed on the lamp body and connected to the three springs present at the triangular base, the lamp can be tilted in any direction, always remaining perfectly balanced. The aluminum swivel LED light source reflector with swivel joint allows directing the light in any position. Dimmable driver on the plug 24V, dimmable.


| Y3 2302 | | Data Sheet | | | |
|--------------------|--------------|------------|--|--|--|
| Family Typology | Y3 Floor | | | | |
| Utilisation | Indoor | | | | |
| Dimensions | | | | | |
| Height | 200 cm | | | | |
| Diameter | 45 (base) cm | | | | |
| Weight | 6.5 Kg | | | | |
| | | | | | |

Materials

| Structure | aluminium | Base | | iron |
|--|--|----------------------------------|-----------------------------------|------|
| Voltage Power unit Mounting Power Supply | 24V Included External | Watt Lumen CRI Duration | 13 W 1950 lm >80 50000 h | |
| Power supply Dimming | Electronic plug-in power supply Dimmer on the cable | CCT Energy class | 3000 К D | |

Certifications





Colour variant code



Black

Y3 2302

Gallery



